

SCT3511

The Mobile Smart Card Dongle



Features

- USB contact smart card reader
- Contactless smart card token*
- Elegant and robust form factor
- ID-000 (SIM card) form factor
- Compliant with major smart cards and relevant industry standards
- Customization options: Casing color and company logo

* in combination with a Plug-in type dual interface card with antenna connection on C4/C8

Operating modes & application examples

PC connected mode

- logical access (secure PC and network log on)
- multiple security applications including PKI, digital signature and personal identification - all in a compact, mobile device

Autonomous mode*

- physical access (to facilities)
- logical access (PC & networks)
- contactless electronic payment
- contactless electronic ticketing
- (public transportation, event ticketing)

* depends on used smart card chip & applications

Dongle Reader

U.S. Headquarters
SCM Microsystems Inc.
41740 Christy Street
Fremont, CA 94538 USA
E-mail scmsales@scmmicro.com
Phone +1 510 360 2300
Fax +1 510 360 0211

European Headquarters
SCM Microsystems GmbH
Oskar-Messter-Str. 13
85737 Ismaning, Germany
E-mail sales@scmmicro.de
Phone +49 89 9595 5000
Fax +49 89 9595 5555

SCM Microsystems Japan, Inc.
GoogolPlex Millennium Building 6F
4-4-20 Shiba, Minato-ku,
Tokyo, Japan 108-0014
E-mail sales@scmmicro.co.jp
Phone +81 3 6414 6611
Fax +81 3 6414 6612

SCM Microsystems India Pvt. Ltd.
Module No. 0506, 0507 & 0508
D' Block South, 5th Floor
Tidel Park, 4 Canal Bank Road
Taramani
Chennai 600113, India
E-mail sales@scmmicro.co.in
Phone +91 44 2254 0020
Fax +91 44 2254 0029

www.scmmicro.com

SCT3511

Technical Data

Interfaces		
Host	USB	• Full speed USB (12Mbps) • USB bus powered device • CCID compliant • USB A-Type connector
Smart Card	contact	• T=0, T=1 protocol support, (ID-000 format) • ISO 7816 class A, B, C support • 8 friction contacts, ID-000 format
	contactless	• Built-in antenna connected to C4 and C8 of smart card module • Accepts dual interface "Plug in Type" cards in ID-000 (SIM) format • ISO 14443, Mifare*
Human	optical	• Green LED
Software	API	• PC/SC, CCID compliant
Operating Systems		• Windows Server 2003, XP, Vista
Power	USB	• Low Bus powered
Dimensions	L x W x H [mm]	• 68.5x24x10
Weight	[g]	• 10
Operating Temperature	[°C]	• 0 - 50
Approvals		• FCC class B, CE class B, VCCI • USB • Certified for Windows, PC/SC
Environmental		• RoHS, WEEE

* if supported by smart card chip

Technical data are subject to change without notice

Availability

- Samples: Limited and available upon request
- Production: Expected end Q12009
(subjected to change with demand)

Ordering Information: sales@scmmicro.com, PN: 905109

The SCM Microsystems' Advantage

Trusted Partner

- ASIC (application specific IC) and smart card reader development experience since 1990
- Innovative solutions - more than 50 patents filed
- Reliable high-quality mass production capability - more than 15 Mio. reader solutions deployed to date
- Active role in standardization committees
- Complex project management expertise
e.g. U.S. Department of Defense CAC program, electronic ID applications (ePassport, health card projects, national ID, driver licence)

Support

- Global presence and support
- Product customization options
- Product branding
- Dedicated Research & Development and customer support team
- Strong global partnership network with leading suppliers along the value chain (smart card manufacturers, application providers, system integrators, device manufacturers)

Trusted Products

- Broadest portfolio of security technology products - for governments, corporations, financial institutions, small and medium-sized enterprises and individuals around the globe
- Secure smart chip reader design - certified and compliant to EMV, Common Criteria, PC/SC, USB
- High-quality products designed to meet the various requirements in the data security area
- Flexible and future proof solutions - SCM's SmartOS™ middleware and its own ASIC technology allow in Field upgrades and secure your investment