



Idaxis™ SecurePIV™ Smart Card Readers

- 4 Innovative Models to Match all Needs
- Fastest ISO 7816 Reader⁽¹⁾
- TAA Compliant
- Custom Logo⁽²⁾

SecurePIV Pro USB



SecurePIV Pro USB-C



SecurePIV mini USB



SecurePIV mini USB-C





Idaxis™ SecurePIV™ Tech Specs

Physical Characteristics	SecurePIV Pro: 66.0mm (L) x 66.0mm (W) x 9.3mm (H) - 48g SecurePIV mini: 58.0mm (L) x 19.0mm (W) x 11.8mm (H) - 11g Casing: Black ABS Supported Card Size: ID-1 (Full size)		
Contact Smart Card Interface	Standard: ISO/IEC 7816 Part 1/2/3/4 Protocol: T=0, T=1, Memory card Supported Card Types: ISO7816 Class A/ B/ C (5V/ 3V/ 1.8V) Power: 55mA in Class A/ B/ C Speed: 9.6 - 826 Kbps Clock Frequency: 4.8 - 16MHz Card Connector: Minimum 100,000 insertion cycles		
USB Interface	USB 2.0 Full Speed (12 Mbps) Operating Power Consumption: <100 mA Standby Power Consumption: <2mA "SecurePIV Pro USB" and "SecurePIV mini USB" connector: USB-A "SecurePIV Pro USB-C" and "SecurePIV mini USB-C" connector: USB-C "SecurePIV Pro USB" and "SecurePIV Pro USB-C" wire length: 1m SecurePIV mini connection: no wire, direct connection to device		
Supported OS	Windows® 7 SP1 and above Linux® Mac OS® 10.12 and above Android™ 6.0 and above		
Compliance & Certifications	ISO/IEC7816 and EMV 2011 Ver 4.3 Level 1 USB 2.0 Full Speed CCID & Microsoft® WHQL Regulatory: EN 60950/IEC 60950, CE, FCC, VCCI, RoHS3, REACH		
US Federal Government	TAA Compliant Compatible with CAC, PIV, PIV-i, TWIC smart cards and others		
Part Numbers & UPC	"SecurePIV Pro USB" "SecurePIV Pro USB-C" "SecurePIV mini USB" "SecurePIV mini USB-C"	P/N: TLP225A P/N: TLP225C P/N: TLP125A P/N: TLP125C	UPC: 0786899878189 UPC: 0786899878196 UPC: 0786899878202 UPC: 0786899878219

Idaxis
1001 Fillmore Street, Suite 3157
Arlington, Virginia 22201, USA
www.idaxis.com
info@idaxis.com

© 2021 Idaxis. All rights reserved. Actual data may differ. Document may be updated without prior notification. All brands and trademarks belong to their respective holders.

(1) Speeds up to 826 kps with TA1=17
(2) With a minimum order of 2000 units